

## SAFETY DATA SHEET

### UNIVERSAL® ALL-SURFACE PAINT - Satin Finish

#### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME UNIVERSAL® ALL-SURFACE PAINT - Satin Finish  
PRODUCT NO. RO00302  
SYNONYMS, TRADE NAMES RO0030201 - White, RO0030202 - Black  
APPLICATION intended for use as a brush- and roller-applied decorative and protective coating for various substrates.  
SUPPLIER Rust-Oleum Corporation  
Portobello Industrial Estate  
Birtley  
County Durham  
DH3 2RE  
+44 (0)191 4106611  
+44 (0)1914920125  
CONTACT PERSON ian.mccormack@tor-coatings.com  
EMERGENCY TELEPHONE +44 207 858 1228 (24-7)

#### 2 HAZARDS IDENTIFICATION

Flammable. Vapours may cause drowsiness and dizziness. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION (1999/45) R10, R52/53, R67.

##### ENVIRONMENT

The product contains a substance which is hazardous to aquatic organisms and which may cause long term adverse effects in the aquatic environment. See section 12.

##### PHYSICAL AND CHEMICAL HAZARDS

The product is flammable, and heating may generate vapours which may form explosive vapour/air mixtures.

##### HUMAN HEALTH

In high concentrations, vapours and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea. Risk of serious damage to eyes. Vapours/aerosol spray may irritate the respiratory system. Repeated exposure may cause skin dryness or cracking. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

#### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content %	Classification (67/548/EEC)
Naptha (Petroleum) Hydrotreated Heavy	265-150-3	64742-48-9	10-25%	Xn;R65. R10,R67.
XYLENE	215-535-7	1330-20-7	5-10%	R10 Xn;R20/21 Xi;R38
Naptha (Petroleum) Hydrodesulphurized Heavy	265-185-4	64742-82-1	5-10%	Xn;R65. N;R51/53. R10,R66,R67.
1-METHOXY-2-PROPANOL	203-539-1	107-98-2	2.5-5.0%	R10
2-METHOXY-1-METHYLETHYL ACETATE	203-603-9	108-65-6	1.0-2.5%	R10 Xi;R36
Hydrocarbons, C9, Aromatics	918-668-5	64742-95-6	< 1%	Xn;R65. Xi;R37. N;R51/53. R10,R66,R67.
BUTYL ACETATE -norm	204-658-1	123-86-4	< 1%	R10 R66 R67
ETHYL METHYL KETOXIME	202-496-6	96-29-7	< 1%	Carc. Cat. 3;R40 Xn;R21 R43 Xi;R41
ISO-BUTANOL	201-148-0	78-83-1	< 1%	R10 Xi;R37/38,R41 R67

The Full Text for all R-Phrases is Displayed in Section 16

#### 4 FIRST-AID MEASURES

##### GENERAL INFORMATION

General first aid, rest, warmth and fresh air. Do not give victim anything to drink if they are unconscious. Get medical attention if any discomfort continues.

##### INHALATION

Place unconscious person on the side in the recovery position and ensure breathing can take place. If respiratory problems, artificial respiration/oxygen. Get medical attention if any discomfort continues.

##### INGESTION

Immediately rinse mouth and drink plenty of water or milk. Keep person under observation. Do not induce vomiting. If vomiting occurs, keep head low. Transport immediately to hospital and bring along these instructions.

**UNIVERSAL® ALL-SURFACE PAINT - Satin Finish****SKIN CONTACT**

Use appropriate hand lotion to prevent defatting and cracking of skin. Immediately remove contaminated clothing. Wash off promptly and flush contaminated skin with water. Promptly remove clothing if soaked through and flush skin with water.

**EYE CONTACT**

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Get medical attention promptly if symptoms occur after washing.

**5 FIRE-FIGHTING MEASURES****EXTINGUISHING MEDIA**

Fire can be extinguished using: Water spray, fog or mist. Foam, carbon dioxide or dry powder. Dry chemicals, sand, dolomite etc. Do not use water jet as an extinguisher, as this will spread the fire.

**SPECIAL FIRE FIGHTING PROCEDURES**

Use pressurised air mask if product is involved in a fire. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

**UNUSUAL FIRE & EXPLOSION HAZARDS**

Fire causes formation of toxic gases.

**PROTECTIVE MEASURES IN FIRE**

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

**6 ACCIDENTAL RELEASE MEASURES****PERSONAL PRECAUTIONS**

Wear protective clothing as described in Section 8 of this safety data sheet.

**ENVIRONMENTAL PRECAUTIONS**

Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

**SPILL CLEAN UP METHODS**

Keep combustibles away from spilled material. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

**7 HANDLING AND STORAGE****USAGE PRECAUTIONS**

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Vapours are heavier than air and may spread near ground to sources of ignition.

**STORAGE PRECAUTIONS**

Flammable/combustible - Keep away from oxidisers, heat and flames. Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container. Avoid contact with oxidising agents.

**STORAGE CLASS**

Flammable liquid storage.

**8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
1-METHOXY-2-PROPANOL	WEL	100 ppm(Sk)	375 mg/m3(Sk)	150 ppm(Sk)	560 mg/m3(Sk)	
2-METHOXY-1-METHYLETHYL ACETATE	WEL	50 ppm(Sk)	274 mg/m3(Sk)	100 ppm(Sk)	548 mg/m3(Sk)	
BUTYL ACETATE -norm	WEL	150 ppm	724 mg/m3	200 ppm	966 mg/m3	
ISO-BUTANOL	WEL	50 ppm	154 mg/m3	75 ppm	231 mg/m3	
Naptha (Petroleum) Hydrodesulphurized Heavy	WEL		600 mg/m3			
Naptha (Petroleum) Hydrotreated Heavy	OES		1000 mg/m3			
XYLENE	WEL	50 ppm(Sk)	220 mg/m3(Sk)	100 ppm(Sk)	441 mg/m3(Sk)	Sk

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through skin.

**INGREDIENT COMMENTS**

WEL = Workplace Exposure Limits

**PROTECTIVE EQUIPMENT**

**UNIVERSAL® ALL-SURFACE PAINT - Satin Finish****PROCESS CONDITIONS**

Provide eyewash station.

**ENGINEERING MEASURES**

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. All handling to take place in well-ventilated area.

**RESPIRATORY EQUIPMENT**

Provide adequate ventilation. Observe Occupational Exposure Limits and minimise the risk of inhalation of vapours. At work in confined or poorly ventilated spaces, respiratory protection with air supply must be used. Wear mask supplied with: Gas cartridge suitable for organic substances.

**HAND PROTECTION**

For prolonged or repeated skin contact use suitable protective gloves. Use protective gloves made of: Neoprene. Nitrile. Rubber (natural, latex).

**EYE PROTECTION**

Wear splash-proof eye goggles to prevent any possibility of eye contact.

**OTHER PROTECTION**

Wear appropriate clothing to prevent any possibility of skin contact.

**HYGIENE MEASURES**

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid
COLOUR	Black. and White.
ODOUR	Mild. Characteristic.
SOLUBILITY	Partially miscible with water.
RELATIVE DENSITY	0.96 - 1.18 Approx. @20°C.
VAPOUR DENSITY (air=1)	Heavier than air
FLASH POINT (°C)	42°C. CC (Closed cup).
FLAMMABILITY LIMIT - LOWER(%)	0.6
FLAMMABILITY LIMIT - UPPER(%)	13.7
VOLATILE ORGANIC COMPOUND (VOC)	Cat A/i : <500 g/l (EU Limit 500 g/l)

## 10 STABILITY AND REACTIVITY

**STABILITY**

No particular stability concerns.

**CONDITIONS TO AVOID**

Avoid heat, flames and other sources of ignition. Avoid contact with strong oxidisers.

**HAZARDOUS DECOMPOSITION PRODUCTS**

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

## 11 TOXICOLOGICAL INFORMATION

**GENERAL INFORMATION**

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

**INHALATION**

In high concentrations, vapours may irritate throat and respiratory system and cause coughing. In high concentrations, vapours are narcotic and may cause headache, fatigue, dizziness and nausea. Gas or vapour is harmful on prolonged exposure or in high concentrations.

**INGESTION**

Gastrointestinal symptoms, including upset stomach. Harmful: may cause lung damage if swallowed. Pneumonia may be the result if vomited material containing solvents reaches the lungs.

**SKIN CONTACT**

Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Irritating to skin. May be absorbed through the skin.

**EYE CONTACT**

Irritation of eyes and mucous membranes.

Name	XYLENE
Toxic Dose 1 - LD 50	3523 mg/kg (oral rat)
Toxic Conc. - LC 50	6191 mg/l/4h (inh-rat)

**UNIVERSAL® ALL-SURFACE PAINT - Satin Finish**

## Other Health Effects

May cause skin and eye irritation.

Name	ISO-BUTANOL
Toxic Dose 1 - LD 50	2460 mg/kg (oral rat)

## Other Health Effects

Toxic through skin absorption. Swallowing may cause severe internal injury, unconsciousness or death. May cause skin/eye irritation and burns (corrosive).

Name	1-METHOXY-2-PROPANOL
------	----------------------

Toxic Dose 1 - LD 50	4016 - 6600 mg/kg (oral rat)
----------------------	------------------------------

Toxic Dose 2 - LD 50	11700 mg/kg (oral-mouse)
----------------------	--------------------------

Toxic Conc. - LC 50	55.0 mg/l/4h (inh-rat)
---------------------	------------------------

Name	BUTYL ACETATE -norm
------	---------------------

Toxic Dose 1 - LD 50	10768 mg/kg (oral rat)
----------------------	------------------------

Toxic Dose 2 - LD 50	3200 mg/kg (oral-rbt)
----------------------	-----------------------

Toxic Conc. - LC 50	390 ppm/4h (inh-rat)
---------------------	----------------------

Name	ETHYL METHYL KETOXIME
------	-----------------------

Toxic Dose 1 - LD 50	2528 mg/kg (oral rat)
----------------------	-----------------------

Toxic Conc. - LC 50	>10.5 mg/l/4h (inh-rat)
---------------------	-------------------------

Name	2-METHOXY-1-METHYLETHYL ACETATE
------	---------------------------------

Toxic Dose 1 - LD 50	5135 mg/kg (oral rat)
----------------------	-----------------------

Name	Naptha (Petroleum) Hydrodesulphurized Heavy
------	---

Toxic Dose 1 - LD 50	>5000 mg/kg (oral rat)
----------------------	------------------------

Name	Naptha (Petroleum) Hydrotreated Heavy
------	---------------------------------------

Toxic Dose 1 - LD 50	>5000 mg/kg (oral rat)
----------------------	------------------------

Name	Hydrocarbons, C9, Aromatics
------	-----------------------------

Toxic Dose 1 - LD 50	3592 mg/kg (oral rat)
----------------------	-----------------------

Toxic Dose 2 - LD 50	3160 mg/kg (oral-rbt)
----------------------	-----------------------

Toxic Conc. - LC 50	6.193 mg/l/4h (inh-rat)
---------------------	-------------------------

**12 ECOLOGICAL INFORMATION**

## ECOTOXICITY

Dangerous for the environment: May cause long-term adverse effects in the aquatic environment.

### UNIVERSAL® ALL-SURFACE PAINT - Satin Finish

Name XYLENE

Partition Coefficient 3.2

#### Ecotoxicity

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment. The product must not be allowed to enter drains or water courses.

LC 50, 72 Hrs, Algae, mg/l 2.2

#### Mobility

Water: Insoluble, the product will spread over the surface and rapidly evaporate. Soil: The product has only slight mobility in the soil and will partially evaporate.

Bioaccumulative potential

Likely to bio-accumulate, but with short retention of the order of a week or less.

#### Degradability

The product is readily biodegradable.

Name ISO-BUTANOL

LC 50, 96 Hrs, Fish mg/l 100-1430

#### Mobility

No specific test data available.

Bioaccumulative potential

The product does not contain any substances expected to be bioaccumulating.

#### Degradability

Readily biodegradeable. Presence in surface waters may present a hazard in terms of Oxygen depletion.

Name 1-METHOXY-2-PROPANOL

#### Ecotoxicity

The substance is rated as practically non-toxic to aquatic species. Do not allow to escape into waterways, wastewater or soil.

LC 50, 96 Hrs, Fish mg/l 6812 - 20800

EC 50, 48 Hrs, Daphnia, mg/l 21100 - 25900

IC 50, 72 Hrs, Algae, mg/l 1000

#### Mobility

The product is soluble in water. Readily absorbed into soil.

Bioaccumulative potential

This material is not expected to significantly bioaccumulate.

#### Degradability

The product is readily biodegradable.

Name BUTYL ACETATE -norm

#### Ecotoxicity

There are no data on the ecotoxicity of this product.

LC 50, 96 Hrs, Fish mg/l 18 - 100

#### Degradability

The product is readily biodegradable.

Name ETHYL METHYL KETOXIME

LC 50, 96 Hrs, Fish mg/l >100

EC 50, 48 Hrs, Daphnia, mg/l 201

IC 50, 72 Hrs, Algae, mg/l 11.8

#### Mobility

The product is water soluble and may spread in water systems.

#### Degradability

>85%

Name 2-METHOXY-1-METHYLETHYL ACETATE

#### Ecotoxicity

The product must not be allowed to enter drains or water courses. Not considered dangerous to aquatic organisms.

LC 50, 96 Hrs, Fish mg/l 100-180

EC 50, 48 Hrs, Daphnia, mg/l 408-500

#### Mobility

Readily absorbed into soil.

Bioaccumulative potential

This material is not expected to significantly bioaccumulate. Log Pow <3 ; BCF <100

#### Degradability

The product is readily biodegradable.

Name Naptha (Petroleum) Hydrodesulphurized Heavy

LC 50, 96 Hrs, Fish mg/l 10

## UNIVERSAL® ALL-SURFACE PAINT - Satin Finish

### Mobility

Water: Insoluble, the product will spread over the surface and rapidly evaporate. Soil: The product has only slight mobility in the soil and will partially evaporate.

Bioaccumulative potential

Likely to bio-accumulate, but with short retention of the order of a week or less.

### Degradability

The product is readily biodegradable.

Name Naptha (Petroleum) Hydrotreated Heavy

LC 50, 96 Hrs, Fish mg/l 2200

### Mobility

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces.

### Degradability

The product is biodegradable.

### Acute Fish Toxicity

Not considered toxic to fish.

Name Hydrocarbons, C9, Aromatics

### Ecotoxicity

Expected to be toxic to aquatic organisms.

LC 50, 96 Hrs, Fish mg/l 9.2

EC 50, 48 Hrs, Daphnia, mg/l 3.2

IC 50, 72 Hrs, Algae, mg/l 2.9

### Mobility

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces.

Bioaccumulative potential

No data available on bioaccumulation.

### Degradability

The product is expected to be biodegradable.

## 13 DISPOSAL CONSIDERATIONS

### GENERAL INFORMATION

Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority.

### DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements. Make sure containers are empty before discarding (explosion risk). Absorb in vermiculite or dry sand and dispose of at a licenced hazardous waste collection point.

## 14 TRANSPORT INFORMATION

### GENERAL

In pack sizes up to and including 30 litres, under the terms of 2.3.2.5, this product is not subject to the packaging, labelling and marking requirements of the IMDG Code, but both full documentation and placarding of cargo transport units is still required.



PROPER SHIPPING NAME	PAINT
ENVIRONMENTALLY HAZARDOUS SUBSTANCE/MARINE POLLUTANT	No.
ADR CLASS	Not dangerous according to ADR.
UN NO. SEA	1263
IMDG CLASS	3
IMDG PACK GR.	III
UN NO. AIR	1263
AIR CLASS	3
AIR PACK GR.	III

## 15 REGULATORY INFORMATION

### RISK PHRASES

R10 Flammable.

## UNIVERSAL® ALL-SURFACE PAINT - Satin Finish

R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67	Vapours may cause drowsiness and dizziness.
SAFETY PHRASES	
S2	Keep out of the reach of children.
S36/37	Wear suitable protective clothing and gloves.
S46	If swallowed, seek medical advice immediately and show this container or label.
S51	Use only in well-ventilated areas.
S56	Dispose of this material and its container to hazardous or special waste collection point.
P14	Contains ETHYL METHYL KETOXIME. May produce an allergic reaction.

### EU DIRECTIVES

System of specific information relating to Dangerous Preparations. 2001/58/EC. Dangerous Preparations Directive 1999/45/EC.

### APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

### NATIONAL REGULATIONS

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689. Workplace Exposure Limits 2005 (EH40)

## 16 OTHER INFORMATION

### INFORMATION SOURCES

Croner's Emergency Spillage Guide Croner's Emergency First Aid Guide Croner's Substances Hazardous to Health

### ISSUED BY

D Charles

REVISION DATE 21/11/2012

REV. NO./REPL. SDS GENERATED 6

SDS NO. 17687

### SAFETY DATA SHEET STATUS

Approved.

DATE 21/11/2012

### RISK PHRASES IN FULL

R10	Flammable.
R20/21	Harmful by inhalation and in contact with skin.
R21	Harmful in contact with skin.
R65	Harmful: may cause lung damage if swallowed.
R36	Irritating to eyes.
R37/38	Irritating to respiratory system and skin.
R37	Irritating to respiratory system.
R38	Irritating to skin.
R40	Limited evidence of a carcinogenic effect.
R43	May cause sensitisation by skin contact.
R66	Repeated exposure may cause skin dryness or cracking.
R41	Risk of serious damage to eyes.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67	Vapours may cause drowsiness and dizziness.

### DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.