

SAFETY DATA SHEET PAINTER'S TOUCH Toy Safe

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME PAINTER'S TOUCH Toy Safe
PRODUCT NO. RO005
SUPPLIER Rust-Oleum Corporation
Portobello Industrial Estate
Birtley
County Durham
DH3 2RE
+44 (0)191 4106611
+44 (0)1914920125
CONTACT PERSON ian.mccormack@tor-coatings.com
EMERGENCY TELEPHONE +44 207 858 1228 (24-7)

2 HAZARDS IDENTIFICATION

CLASSIFICATION (1999/45) Not classified.
CLASSIFICATION (EC 1272/2008)
Physical and Chemical Hazards Not classified.
Human health Not classified.
Environment Not classified.

LABEL IN ACCORDANCE WITH (EC) NO. 1272/2008
Not classified.

PRECAUTIONARY STATEMENTS

P102 Keep out of reach of children.
P281 Use personal protective equipment as required.
P302+352 IF ON SKIN: Wash with plenty of soap and water.
P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

ENVIRONMENT

The product is not expected to be hazardous to the environment.

HUMAN HEALTH

Prolonged contact may cause redness, irritation and dry skin. Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Dipropylene Glycol Monomethyl Ether	1.0-2.5%
CAS-No.: 34590-94-8	EC No.: 252-104-2
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.
2-(2-BUTOXYETHOXY)ETHANOL	< 1%
CAS-No.: 112-34-5	EC No.: 203-961-6
Classification (EC 1272/2008) Eye Irrit. 2 - H319	Classification (67/548/EEC) Xi:R36

The Full Text for all R-Phrases and Hazard Statements is Displayed in Section 16

4 FIRST-AID MEASURES

GENERAL INFORMATION

General first aid, rest, warmth and fresh air. Do not give victim anything to drink if they are unconscious. Get medical attention if any discomfort continues.

PAINTER'S TOUCH Toy Safe

INHALATION

Place unconscious person on the side in the recovery position and ensure breathing can take place. If respiratory problems, artificial respiration/oxygen. Get medical attention if any discomfort continues.

INGESTION

Immediately rinse mouth and drink plenty of water or milk. Keep person under observation. Do not induce vomiting. If vomiting occurs, keep head low. Transport immediately to hospital and bring along these instructions.

SKIN CONTACT

Use appropriate hand lotion to prevent defatting and cracking of skin. Immediately remove contaminated clothing. Wash off promptly and flush contaminated skin with water. Promptly remove clothing if soaked through and flush skin with water.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Get medical attention promptly if symptoms occur after washing.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

SPECIAL FIRE FIGHTING PROCEDURES

Use pressurised air mask if product is involved in a fire. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

UNUSUAL FIRE & EXPLOSION HAZARDS

Fire causes formation of toxic gases.

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

ENVIRONMENTAL PRECAUTIONS

Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

SPILL CLEAN UP METHODS

Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container. Avoid contact with oxidising agents.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
2-(2-BUTOXYETHOXY)ETHANOL		10 ppm	67.5 mg/m3	15 ppm	101.2 mg/m3	
Dipropylene Glycol Monomethyl Ether	OES		600 mg/m3			

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT



PROCESS CONDITIONS

Provide eyewash station.

ENGINEERING MEASURES

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. All handling to take place in well-ventilated area.

PAINTER'S TOUCH Toy Safe**RESPIRATORY EQUIPMENT**

Provide adequate ventilation. Observe Occupational Exposure Limits and minimise the risk of inhalation of vapours.

HAND PROTECTION

Protective gloves should be used if there is a risk of direct contact or splash.

EYE PROTECTION

Wear splash-proof eye goggles to prevent any possibility of eye contact.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid
COLOUR	Selected range.
ODOUR	Mild.
SOLUBILITY	Miscible with water
RELATIVE DENSITY	1.0 - 1.3 Approx. (depending on colour) @20°C.
VAPOUR DENSITY (air=1)	Heavier than air

10 STABILITY AND REACTIVITY**STABILITY**

No particular stability concerns.

HAZARDOUS DECOMPOSITION PRODUCTS

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

11 TOXICOLOGICAL INFORMATION**GENERAL INFORMATION**

Not regarded as a health hazard under current legislation.

Name	2-(2-BUTOXYETHOXY)ETHANOL
Toxic Dose 1 - LD 50	4500 - 5660 mg/kg (oral rat)
Toxic Dose 2 - LD 50	2400 - 6050 mg/kg (oral-mouse)
Name	Dipropylene Glycol Monomethyl Ether
Toxic Dose 1 - LD 50	21000 - 34000 mg/kg (oral rat)
Toxic Dose 2 - LD 50	>20000 mg/kg (oral-rbt)

12 ECOLOGICAL INFORMATION**ECOTOXICITY**

The product is not expected to be hazardous to the environment.

PAINTER'S TOUCH Toy Safe

Name 2-(2-BUTOXYETHOXY)ETHANOL

Ecotoxicity

The product contains a substance which causes risk of hazardous effects to the environment.

LC 50, 96 Hrs, Fish mg/l 1300

EC 50, 48 Hrs, Daphnia, mg/l 100

Mobility

The product is soluble in water.

Bioaccumulative potential

This material is not expected to significantly bioaccumulate.

Degradability

The product is moderately biodegradable.

Name Dipropylene Glycol Monomethyl Ether

LC 50, 96 Hrs, Fish mg/l 4000 - 54600

EC 50, 48 Hrs, Daphnia, mg/l 4850 - 34400

IC 50, 72 Hrs, Algae, mg/l >100

Mobility

The product is soluble in water. Mobile.

Bioaccumulative potential

This material is not expected to significantly bioaccumulate.

Degradability

The product is readily biodegradable.

13 DISPOSAL CONSIDERATIONS

GENERAL INFORMATION

Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority.

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements. Absorb in vermiculite or dry sand and dispose of at a licensed hazardous waste collection point.

14 TRANSPORT INFORMATION

GENERAL

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

No transport warning sign required.

ENVIRONMENTALLY HAZARDOUS SUBSTANCE/MARINE POLLUTANT

No.

15 REGULATORY INFORMATION

EU DIRECTIVES

System of specific information relating to Dangerous Preparations. 2001/58/EC. Dangerous Preparations Directive 1999/45/EC.

APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

NATIONAL REGULATIONS

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689. Workplace Exposure Limits 2005 (EH40)

16 OTHER INFORMATION

INFORMATION SOURCES

Croner's Emergency Spillage Guide Croner's Emergency First Aid Guide Croner's Substances Hazardous to Health

ISSUED BY

I McCormack

REVISION DATE 02/12/2004

REV. NO./REPL. SDS GENERATED 1

SDS NO. 18397

SAFETY DATA SHEET STATUS

Approved.

DATE 21/11/2012

RISK PHRASES IN FULL

R36 Irritating to eyes.

NC Not classified.

PAINTER'S TOUCH Toy Safe

HAZARD STATEMENTS IN FULL

H319 Causes serious eye irritation.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.