

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : Automotive Lacquer  
**Product description** : Aerosol. Paint.  
**Product type** : Aerosol.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

| Identified uses                                       |        |
|---|--------|
| Industrial uses<br>Consumer uses<br>Professional uses |        |
| Uses advised against                                  | Reason |
| None identified.                                      | -      |

### 1.3 Details of the supplier of the safety data sheet

Rust-Oleum Corporation  
 Portobello Industrial Estate  
 Birtley  
 County Durham  
 United Kingdom  
 DH3 2RE  
 Telephone no.: +44 (0) 191 4106611  
 Fax no.: +44 (0) 191 4920125

**e-mail address of person responsible for this SDS** : rpmeurohas@ro-m.com

### 1.4 Emergency telephone number

#### Supplier

**Telephone number** : +44 (0) 207 858 1228  
**Hours of operation** : 24 / 7

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aerosol 1, H222, H229  
 Skin Irrit. 2, H315  
 Eye Irrit. 2, H319  
 STOT SE 3, H336  
 STOT RE 2, H373

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

## SECTION 2: Hazards identification

**Hazard pictograms** :



**Signal word** :

Danger

**Hazard statements** :

Extremely flammable aerosol.  
 Causes serious eye irritation.  
 Causes skin irritation.  
 May cause drowsiness or dizziness.  
 May cause damage to organs through prolonged or repeated exposure.  
 Pressurized container: may burst if heated.

**Precautionary statements**

**General** :

Keep out of reach of children. Read label before use. If medical advice is needed, have product container or label at hand.

**Prevention** :

Do not breathe vapour or spray. Use only outdoors or in a well-ventilated area. Wear protective gloves and eye protection: nitrile rubber gloves and Safety glasses with side shields. Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.

**Response** :

IF ON SKIN: Wash with plenty of soap and water.

**Storage** :

Store locked up. Protect from sunlight and do not expose to temperatures exceeding 50 °C.

**Disposal** :

Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Hazardous ingredients** :

acetone  
 xylene (mixture of isomers)

**Supplemental label elements** :

Contains benzotriazole derivatives mix. May produce an allergic reaction.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** :

Not applicable.

**Special packaging requirements**

**Containers to be fitted with child-resistant fastenings** :

Not applicable.

**Tactile warning of danger** :

Yes, applicable.

**2.3 Other hazards**

**Other hazards which do not result in classification** :

None known.

## SECTION 3: Composition/information on ingredients

**3.2 Mixtures** :

Mixture

**SECTION 3: Composition/information on ingredients**

| Product/ingredient name         | Identifiers   | %         | Classification   |   | Type    |
|---------------------------------|---|-----------|--|---|---------|
|                                 |   |           | 67/548/EEC   | Regulation (EC) No. 1272/2008 [CLP]   |         |
| acetone                         | REACH #:<br>01-2119471330-49<br>EC: 200-662-2<br>CAS: 67-64-1<br>Index: 606-001-00-8  | ≥25 - <50 | F; R11   | Flam. Liq. 2, H225  | [1] [2] |
| xylene (mixture of isomeres)    | REACH #:<br>01-2119488216-32<br>EC: 215-535-7<br><br>CAS: 1330-20-7                   | ≥10 - <25 | R10<br><br>Xn; R20/21, R48/20, R65<br>Xi; R36/37/38  | Eye Irrit. 2, H319<br>STOT SE 3, H336<br>EUH066<br>Flam. Liq. 3, H226<br><br>Acute Tox. 4, H312<br><br>Acute Tox. 4, H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>STOT SE 3, H335<br>STOT RE 2, H373<br>Asp. Tox. 1, H304<br>Flam. Liq. 3, H226 | [1] [2] |
| n-butyl acetate                 | REACH #:<br>01-2119485493-29<br>EC: 204-658-1<br>CAS: 123-86-4<br>Index: 607-025-00-1 | ≥5 - <10  | R10<br><br>R66, R67  | STOT SE 3, H336<br>EUH066   | [1] [2] |
| butane                          | EC: 203-448-7<br>CAS: 106-97-8<br>Index: 601-004-00-0                                 | ≥5 - <10  | F+; R12  | Flam. Gas 1, H220   | [2]     |
| 2-methoxy-1-methylethyl acetate | REACH #:<br>01-2119475791-29<br>EC: 203-603-9<br>CAS: 108-65-6<br>Index: 607-195-00-7 | ≥3 - <5   | R10  | Flam. Liq. 3, H226  | [2]     |
| benzotriazole derivatives mix   | EC: 400-830-7<br><br>CAS: -   | ≥0.3 - <1 | R43<br><br>N; R51/53<br><br><b>See Section 16 for the full text of the R-phrases declared above.</b> | Skin Sens. 1, H317<br><br>Aquatic Chronic 2, H411<br><br><b>See Section 16 for the full text of the H statements declared above.</b>  | [1]     |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains benzotriazole derivatives mix. May produce an allergic reaction.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

See toxicological information (Section 11)

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders, water spray.
- Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

## SECTION 5: Firefighting measures

**Hazardous thermal decomposition products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

### 5.3 Advice for firefighters

**Special protective actions for fire-fighters** : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

**Special protective equipment for fire-fighters** : Appropriate breathing apparatus may be required.

**Additional information** : Pressurised container: protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. Do not puncture, incinerate or store the container at temperatures above 49°C (120°F) or in direct sunlight. Container explosion may occur under fire conditions or when heated. Bursting aerosol containers may be propelled from a fire at high speed.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and material for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

### 6.4 Reference to other sections

: See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

### 7.1 Precautions for safe handling

: Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the

## SECTION 7: Handling and storage

conducting type.

Keep away from heat, sparks and flame. No sparking tools should be used.

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see Section 8).

Never use pressure to empty. Container is not a pressure vessel.

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

Do not allow to enter drains or watercourses.

### Information on fire and explosion protection

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

#### Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

#### Additional information on storage conditions

Observe label precautions. Do not store above the following temperature: 35°C (95°F). Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

### Seveso Directive - Reporting thresholds (in tonnes)

#### Danger criteria

| Category  | Notification and MAPP threshold | Safety report threshold |
|---|---------------------------------|-------------------------|
| P3a: Flammable aerosols containing flammable gases or flammable liquids | 150                             | 500                     |

### 7.3 Specific end use(s)

**Recommendations** : Not available.

**Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

#### Occupational exposure limits

## SECTION 8: Exposure controls/personal protection

| Product/ingredient name         | Exposure limit values   |
|---------------------------------|---|
| acetone                         | <b>EH40/2005 WELs (United Kingdom (UK), 12/2011).</b><br>STEL: 3620 mg/m <sup>3</sup> 15 minutes.<br>STEL: 1500 ppm 15 minutes.<br>TWA: 500 ppm 8 hours.<br>TWA: 1210 mg/m <sup>3</sup> 8 hours.                    |
| xylene (mixture of isomeres)    | <b>EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin.</b><br>STEL: 441 mg/m <sup>3</sup> 15 minutes.<br>STEL: 100 ppm 15 minutes.<br>TWA: 220 mg/m <sup>3</sup> 8 hours.<br>TWA: 50 ppm 8 hours. |
| n-butyl acetate                 | <b>EH40/2005 WELs (United Kingdom (UK), 12/2011).</b><br>STEL: 966 mg/m <sup>3</sup> 15 minutes.<br>STEL: 200 ppm 15 minutes.<br>TWA: 724 mg/m <sup>3</sup> 8 hours.<br>TWA: 150 ppm 8 hours.                       |
| butane                          | <b>EH40/2005 WELs (United Kingdom (UK), 12/2011).</b><br>STEL: 1810 mg/m <sup>3</sup> 15 minutes.<br>STEL: 750 ppm 15 minutes.<br>TWA: 1450 mg/m <sup>3</sup> 8 hours.<br>TWA: 600 ppm 8 hours.                     |
| 2-methoxy-1-methylethyl acetate | <b>EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin.</b><br>STEL: 548 mg/m <sup>3</sup> 15 minutes.<br>STEL: 100 ppm 15 minutes.<br>TWA: 274 mg/m <sup>3</sup> 8 hours.<br>TWA: 50 ppm 8 hours. |

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### DNELs/DMELs

| Product/ingredient name | Type | Exposure               | Value                   | Population | Effects  |
|-------------------------|------|------------------------|-------------------------|------------|----------|
| n-butyl acetate         | DNEL | Long term Dermal       | 7 mg/kg bw/day          | Workers    | Systemic |
|                         | DNEL | Long term Oral, Dermal | 3.4 mg/kg bw/day        | Consumers  | Systemic |
|                         | DNEL | Short term Inhalation  | 960 mg/m <sup>3</sup>   | Workers    | Systemic |
|                         | DNEL | Short term Inhalation  | 960 mg/m <sup>3</sup>   | Workers    | Local    |
|                         | DNEL | Long term Inhalation   | 480 mg/m <sup>3</sup>   | Workers    | Systemic |
|                         | DNEL | Long term Inhalation   | 480 mg/m <sup>3</sup>   | Workers    | Local    |
|                         | DNEL | Short term Inhalation  | 859.7 mg/m <sup>3</sup> | Consumers  | Systemic |
|                         | DNEL | Short term Inhalation  | 859.7 mg/m <sup>3</sup> | Consumers  | Local    |

## SECTION 8: Exposure controls/personal protection

|                                 |      |                      |                          |           |          |
|---------------------------------|------|----------------------|--------------------------|-----------|----------|
| 2-methoxy-1-methylethyl acetate | DNEL | Long term Inhalation | 102.34 mg/m <sup>3</sup> | Consumers | Systemic |
|                                 | DNEL | Long term Inhalation | 102.34 mg/m <sup>3</sup> | Consumers | Local    |
|                                 | DNEL | Long term Inhalation | 275 mg/m <sup>3</sup>    | Workers   | Systemic |
|                                 | DNEL | Long term Dermal     | 153.5 mg/m <sup>3</sup>  | Workers   | Systemic |
|                                 | DNEL | Long term Dermal     | 54.8 mg/m <sup>3</sup>   | Consumers | Systemic |
|                                 | DNEL | Long term Oral       | 1.67 mg/m <sup>3</sup>   | Consumers | Systemic |

### PNECs

| Product/ingredient name | Compartment Detail              | Value        | Method Detail |
|-------------------------|---------------------------------|--------------|---------------|
| n-butyl acetate         | Fresh water                     | 0.18 mg/l    | -             |
|                         | Marine                          | 0.018 mg/l   | -             |
|                         | Fresh water sediment            | 0.981 mg/kg  | -             |
|                         | Marine water sediment           | 0.0981 mg/kg | -             |
|                         | Soil                            | 0.0903 mg/kg | -             |
|                         | Sewage Treatment Plant          | 35.6 mg/l    | -             |
|                         | 2-methoxy-1-methylethyl acetate | Fresh water  | 0.635 mg/l    |
| Fresh water sediment    |                                 | 3.29 mg/kg   | -             |
| Marine water sediment   |                                 | 0.329 mg/kg  | -             |
| Soil                    |                                 | 0.29 mg/kg   | -             |
| Sewage Treatment Plant  |                                 | 100 mg/l     | -             |

## 8.2 Exposure controls

**Appropriate engineering controls** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. Recommended: safety glasses with side-shields (EN 166).

### Skin protection

#### Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.



## SECTION 8: Exposure controls/personal protection

- Gloves** : For prolonged or repeated handling, use the following type of gloves:
- Recommended: > 8 hours (breakthrough time): Rubber gloves., nitrile rubber (0.5mm) .
- The recommendation for the type or types of glove to use when handling this product is based on information from the following source:
- EN 374-3 : 2003
- The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods. Recommended: Overalls buttoned to the neck and wrist. (EN 1149-1)
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: organic vapour (Type AX) and particulate filter (EN 140) .
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid. [Aerosol.]
- Colour** : Various
- Odour** : Hydrocarbon. Characteristic.
- Odour threshold** : Not available.
- pH** : Not available.
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** : Not available.
- Flash point** : Closed cup: -104°C
- Evaporation rate** : Not available.
- Flammability (solid, gas)** : Flammable in the presence of the following materials or conditions: open flames, sparks and static discharge and heat.  
Slightly flammable in the presence of the following materials or conditions: shocks and mechanical impacts.  
In use, may form flammable/explosive vapour-air mixture. Vapour may travel a considerable distance to source of ignition and flash back.
- Upper/lower flammability or explosive limits** : Lower: 0.8%  
Upper: 9%
- Vapour pressure** : 420 kPa [room temperature]
- Vapour density** : >1 [Air = 1]
- Relative density** : 0.88 to 0.98

## SECTION 9: Physical and chemical properties

- Solubility(ies)** : Insoluble in the following materials: cold water and hot water.
- Partition coefficient: n-octanol/ water** : Not available.
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- Viscosity** : Not available.
- Explosive properties** : Extremely explosive in the presence of the following materials or conditions: open flames, sparks and static discharge and heat.  
Pressurised container: protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. Do not puncture, incinerate or store the container at temperatures above 49°C (120°F) or in direct sunlight. Container explosion may occur under fire conditions or when heated. Bursting aerosol containers may be propelled from a fire at high speed.
- Oxidising properties** : Not available.

### 9.2 Other information

#### Aerosol product

- Type of aerosol** : Spray
- Heat of combustion** : 29.15 kJ/g

No additional information.

## SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : Stable under recommended storage and handling conditions (see Section 7).
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.
- 10.5 Incompatible materials** : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
- 10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced. If involved in a fire, toxic gases including CO, CO<sub>2</sub> and smoke can be generated.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

## SECTION 11: Toxicological information

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains benzotriazole derivatives mix. May produce an allergic reaction.

### Acute toxicity

| Product/ingredient name         | Result                       | Species | Dose                   | Exposure |
|---------------------------------|------------------------------|---------|------------------------|----------|
| acetone                         | LD50 Oral                    | Rat     | 5800 mg/kg             | -        |
|                                 | xylene (mixture of isomeres) | Rat     | 5000 ppm               | 4 hours  |
| n-butyl acetate                 | LC50 Inhalation Gas.         | Rat     | 6670 ppm               | 4 hours  |
|                                 | LD50 Oral                    | Rat     | 4300 mg/kg             | -        |
|                                 | TDLo Dermal                  | Rabbit  | 4300 mg/kg             | -        |
|                                 | LC50 Inhalation Vapour       | Rat     | >21 mg/l               | 4 hours  |
|                                 | LC50 Inhalation Vapour       | Rat     | 9700 mg/m <sup>3</sup> | 4 hours  |
|                                 | LD50 Dermal                  | Rabbit  | >17600 mg/kg           | -        |
| 2-methoxy-1-methylethyl acetate | LD50 Oral                    | Rat     | 14000 mg/kg            | -        |
|                                 | LC50 Inhalation Vapour       | Rat     | 4345 mg/l              | 6 hours  |
|                                 | LD50 Dermal                  | Rabbit  | >5 g/kg                | -        |
|                                 | LD50 Oral                    | Rat     | 8532 mg/kg             | -        |

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Acute toxicity estimates

Not available.

### Irritation/Corrosion

| Product/ingredient name      | Result  | Species | Score | Exposure                 | Observation |
|------------------------------|---|---------|-------|--------------------------|-------------|
| acetone                      | Eyes - Mild irritant                          | Human   | -     | 186300 parts per million | -           |
|                              | Eyes - Mild irritant                          | Rabbit  | -     | 10 microliters           | -           |
|                              | Eyes - Moderate irritant                      | Rabbit  | -     | 24 hours 20 milligrams   | -           |
|                              | Eyes - Severe irritant                        | Rabbit  | -     | 20 milligrams            | -           |
|                              | Skin - Mild irritant                          | Rabbit  | -     | 24 hours 500 milligrams  | -           |
| xylene (mixture of isomeres) | Skin - Mild irritant                          | Rabbit  | -     | 395 milligrams           | -           |
|                              | Eyes - Mild irritant                          | Rabbit  | -     | 87 milligrams            | -           |
|                              | Eyes - Severe irritant                        | Rabbit  | -     | 24 hours 5 milligrams    | -           |
|                              | Skin - Mild irritant                          | Rat     | -     | 8 hours 60 microliters   | -           |
|                              | Skin - Moderate irritant                      | Rabbit  | -     | 24 hours 500 milligrams  | -           |
| n-butyl acetate              | Skin - Moderate irritant                      | Rabbit  | -     | 100 Percent              | -           |
|                              | Eyes - Moderate irritant                      | Rabbit  | -     | 100 milligrams           | -           |
|                              | Skin - Moderate irritant                      | Rabbit  | -     | 24 hours 500 milligrams  | -           |
|                              | Skin - Primary dermal irritation index (PDII) | Rabbit  | 0     | -                        | -           |
|                              | Eyes - Cornea opacity                         | Rabbit  | 1     | -                        | -           |

### Conclusion/Summary

**Skin** : Causes skin irritation.

**Eyes** : Causes serious eye irritation.

**Respiratory** : May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure if inhaled.

### Sensitisation

### Conclusion/Summary

## SECTION 11: Toxicological information

**Skin** : Based on available data, the classification criteria are not met.

**Respiratory** : Based on available data, the classification criteria are not met.

### Mutagenicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Carcinogenicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Reproductive toxicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Teratogenicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Specific target organ toxicity (single exposure)

| Product/ingredient name      | Category   | Route of exposure | Target organs                |
|------------------------------|------------|-------------------|------------------------------|
| acetone                      | Category 3 | Not applicable.   | Narcotic effects             |
| xylene (mixture of isomeres) | Category 3 | Not applicable.   | Respiratory tract irritation |
| n-butyl acetate              | Category 3 | Not applicable.   | Narcotic effects             |

### Specific target organ toxicity (repeated exposure)

| Product/ingredient name      | Category   | Route of exposure | Target organs  |
|------------------------------|------------|-------------------|----------------|
| xylene (mixture of isomeres) | Category 2 | Not determined    | Not determined |

### Aspiration hazard

| Product/ingredient name      | Result                         |
|------------------------------|--------------------------------|
| xylene (mixture of isomeres) | ASPIRATION HAZARD - Category 1 |

**Other information** : Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

There are no data available on the mixture itself.  
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as hazardous to the environment, but contains substance(s) hazardous to the environment. See section 3 for details.

| Product/ingredient name         | Result                                   | Species                                    | Exposure |
|---------------------------------|--|--|----------|
| acetone                         | Acute LC50 8.64 to 8098 mg/l Fresh water | Crustaceans - Ceriodaphnia dubia - Neonate | 48 hours |
|                                 | Acute LC50 7.88 to 7280 mg/l Fresh water | Fish - Pimephales promelas                 | 96 hours |
| n-butyl acetate                 | Acute EC10 956 mg/l                      | Bacteria - Pseudomonas putida              | 18 hours |
|                                 | Acute EC50 648 mg/l                      | Algae - Desmodesmus subspicatus            | 72 hours |
|                                 | Acute LC50 32 mg/l Marine water          | Crustaceans - Artemia salina - Nauplii     | 48 hours |
|                                 | Acute LC50 18 mg/l Fresh water           | Fish - Pimephales promelas                 | 96 hours |
| 2-methoxy-1-methylethyl acetate | Acute LC50 62 mg/l                       | Fish - Danio rerio                         | 96 hours |
|                                 | Acute EC50 408 to 500 mg/l               | Daphnia spec.                              | 48 hours |
|                                 | Acute LC50 161 mg/l                      | Fish                                       | 96 hours |
|                                 | Acute LC50 100 to 180 mg/l               | Fish                                       | 96 hours |

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

**SECTION 12: Ecological information****12.2 Persistence and degradability**

| Product/ingredient name      | Test | Result                   | Dose | Inoculum |
|------------------------------|------|--------------------------|------|----------|
| xylene (mixture of isomeres) | -    | 90 % - Readily - 5 days  | -    | -        |
| n-butyl acetate              | -    | 90 % - Readily - 28 days | -    | -        |

**Conclusion/Summary** : Based on available data, the classification criteria are not met. This product has not been tested for biodegradation.

| Product/ingredient name         | Aquatic half-life | Photolysis | Biodegradability |
|---------------------------------|-------------------|------------|------------------|
| acetone                         | -                 | -          | Readily          |
| xylene (mixture of isomeres)    | -                 | -          | Readily          |
| n-butyl acetate                 | -                 | -          | Readily          |
| 2-methoxy-1-methylethyl acetate | -                 | -          | Readily          |

**12.3 Bioaccumulative potential**

| Product/ingredient name         | LogP <sub>ow</sub> | BCF | Potential |
|---------------------------------|--------------------|-----|-----------|
| acetone                         | -0.27 to 0.58      | -   | low       |
| xylene (mixture of isomeres)    | 3,16               | -   | low       |
| n-butyl acetate                 | 2,3                | 10  | low       |
| 2-methoxy-1-methylethyl acetate | 0,43               | -   | low       |

**12.4 Mobility in soil**

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Volatile.

**12.5 Results of PBT and vPvB assessment**

**PBT** : Not applicable.

**vPvB** : Not applicable.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

**SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance.

**13.1 Waste treatment methods****Product**

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Yes.

**Disposal considerations** : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

**European waste catalogue (EWC)**

## SECTION 13: Disposal considerations

The European Waste Catalogue classification of this product, when disposed of as waste, is:

| Waste code | Waste designation   |
|------------|---|
| 20 01 27*  | paint, inks, adhesives and resins containing dangerous substances |


### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Disposal considerations** : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

**Special precautions** : This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

## SECTION 14: Transport information

|  | ADR/RID   | ADN                                   | IMDG  | IATA   |
|--|---|---------------------------------------|---|--|
| <b>14.1 UN number</b>                  | UN 1950   | UN 1950                               | UN 1950   | UN 1950  |
| <b>14.2 UN proper shipping name</b>    | AEROSOLS, Flammable [Limited quantity]  | AEROSOLS Flammable [Limited quantity] | AEROSOLS Flammable [Limited quantity]   | AEROSOLS, Flammable  |
| <b>14.3 Transport hazard class(es)</b> | 2   | 2                                     | 2.1   | 2.1<br>   |
| <b>14.4 Packing group</b>              | -   | -                                     | -   | -  |
| <b>14.5 Environmental hazards</b>      | No.   | No.                                   | No.   | No.  |
| <b>Additional information</b>          | <p><b>Limited quantity:</b><br/>LQ2</p> <p><b>Remarks:</b><br/>(≤ 1L: ) Limited Quantity - ADR/IMDG 3.4</p> <p>ADR Tunnel code: (D)</p> |                                       | <p><b>Emergency schedules (EmS):</b><br/>F-D + S-U</p> <p><b>Remarks:</b><br/>Limited Quantity - ADR/IMDG 3.4</p> | <p><b>Passenger and Cargo Aircraft</b><br/>Quantity limitation: 75 kg<br/>Packaging instructions: 203</p> <p><b>Cargo Aircraft Only</b><br/>Quantity limitation: 150 kg<br/>Packaging instructions: 203</p> <p><b>Limited Quantities - Passenger Aircraft</b><br/>Quantity limitation: 30 kg<br/>Packaging instructions: Y 203</p> |

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Automotive Lacquer

## SECTION 14: Transport information

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

##### Annex XIV - List of substances subject to authorisation

###### Annex XIV

None of the components are listed.

###### Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

#### Other EU regulations

- VOC** : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.
- VOC for Ready-for-Use Mixture** : IIB/e. Special finishes - All types. EU limit value for this product : 840g/l. (2007) This product contains a maximum of 675 g/l VOC.
- Europe inventory** : All components are listed or exempted.
- Priority List Chemicals (793/93/EEC)** : Listed
- Integrated pollution prevention and control list (IPPC) - Air** : Listed
- Aerosol dispensers** :

3



Extremely flammable

#### Seveso Directive

This product is controlled under the Seveso Directive.

#### Danger criteria

##### Category

P3a: Flammable aerosols containing flammable gases or flammable liquids

#### National regulations

**Industrial use** : The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

| Product/ingredient name | List name                                  | Name on list | Classification | Notes |
|-------------------------|--|--------------|----------------|-------|
| butane                  | UK Occupational Exposure Limits EH40 - WEL | butane       | Carc.          | -     |

## SECTION 15: Regulatory information

**References** : EH40/2005 Workplace exposure limits  
 Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by  
 Regulation (EU) No. 2015/830

**International regulations**

**Chemical Weapon Convention List Schedules I, II & III Chemicals**

Not listed.

**Montreal Protocol (Annexes A, B, C, E)**

Not listed.

**Stockholm Convention on Persistent Organic Pollutants**

Not listed.

**Rotterdam Convention on Prior Inform Consent (PIC)**

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

**CN code** : 3208 10 90

**International lists**

**National inventory**

- Australia** : Not determined.
- Canada** : Not determined.
- China** : Not determined.
- Japan** : Not determined.
- Malaysia** : Not determined.
- New Zealand** : Not determined.
- Philippines** : Not determined.
- Republic of Korea** : Not determined.
- Taiwan** : Not determined.
- United States** : Not determined.

**15.2 Chemical Safety Assessment** : No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

Indicates information that has changed from previously issued version.

**Abbreviations and acronyms**

- : ATE = Acute Toxicity Estimate
- : CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- : DMEL = Derived Minimal Effect Level
- : DNEL = Derived No Effect Level
- : EUH statement = CLP-specific Hazard statement
- : PBT = Persistent, Bioaccumulative and Toxic
- : PNEC = Predicted No Effect Concentration
- : RRN = REACH Registration Number
- : vPvB = Very Persistent and Very Bioaccumulative

**Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

| Classification        | Justification   |
|-----------------------|-----------------|
| Aerosol 1, H222, H229 | Expert judgment |
| Skin Irrit. 2, H315   | Expert judgment |
| Eye Irrit. 2, H319    | Expert judgment |
| STOT SE 3, H336       | Expert judgment |
| STOT RE 2, H373       | Expert judgment |



## SECTION 16: Other information

|  |  |  |
|--|--|--|
| <b>Full text of abbreviated H statements</b> | : H220<br>H222, H229<br><br>H225<br>H226<br>H304<br>H312 (dermal)<br>H315<br>H317<br>H319<br>H332 (inhalation)<br>H335<br>H336<br>H373<br><br>H411 | Extremely flammable gas.<br>Extremely flammable aerosol. Pressurized container: may burst if heated.<br>Highly flammable liquid and vapour.<br>Flammable liquid and vapour.<br>May be fatal if swallowed and enters airways.<br>Harmful in contact with skin.<br>Causes skin irritation.<br>May cause an allergic skin reaction.<br>Causes serious eye irritation.<br>Harmful if inhaled.<br>May cause respiratory irritation.<br>May cause drowsiness or dizziness.<br>May cause damage to organs through prolonged or repeated exposure.<br>Toxic to aquatic life with long lasting effects. |
|--|--|--|

|   |  |  |
|---|--|--|
| <b>Full text of classifications [CLP/GHS]</b> | : Acute Tox. 4, H312<br>Acute Tox. 4, H332<br>Aerosol 1, H222, H229<br>Aquatic Chronic 2, H411<br>Asp. Tox. 1, H304<br>EUH066<br>Eye Irrit. 2, H319<br><br>Flam. Gas 1, H220<br>Flam. Liq. 2, H225<br>Flam. Liq. 3, H226<br>Skin Irrit. 2, H315<br>Skin Sens. 1, H317<br>STOT RE 2, H373<br><br>STOT SE 3, H335<br><br>STOT SE 3, H336 | ACUTE TOXICITY (dermal) - Category 4<br>ACUTE TOXICITY (inhalation) - Category 4<br>AEROSOLS - Category 1<br>LONG-TERM AQUATIC HAZARD - Category 2<br>ASPIRATION HAZARD - Category 1<br>Repeated exposure may cause skin dryness or cracking.<br>SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2<br><br>FLAMMABLE GASES - Category 1<br>FLAMMABLE LIQUIDS - Category 2<br>FLAMMABLE LIQUIDS - Category 3<br>SKIN CORROSION/IRRITATION - Category 2<br>SKIN SENSITIZATION - Category 1<br>SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2<br>SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3<br>SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 |
|---|--|--|

**Date of printing** : 22/09/2016  
**Date of issue/ Date of revision** : 21/09/2016  
**Date of previous issue** : No previous validation  
**Version** : 2

### Notice to reader

The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.