

Technical Data Sheet

Rust-Oleum Metal Expert Water-based Garage Door Paint (750ml)

An ultra-durable, corrosion resistant finish for garage doors. An acrylic formula with excellent colour retention properties. Apply directly to ferrous metal, no primer needed.

- **Water-based**
- **Ultra durable**
- **Corrosion resistant**
- **Excellent colour retention**

Rust-Oleum Metal Expert Water-based Garage Door Paint can also be used on suitably primed wood, masonry, UPVC, plastic, concrete and cladding. For non-ferrous and galvanised metal prime first with a suitable primer.

Rust-Oleum® Metal Expert Garage Door Paint sheds water and is mould resistant, containing a biocide to protect the dried coating from fungal degradation.

Preparation: Remove oil, grease and all other surface contamination by cleaning with appropriate detergents. Remove loose rust by scraping and wire brushing or sanding.

Application: Stir thoroughly prior to use. The product may be applied by brush, roller or electric paint sprayer. If rolling, use a short to medium nap mohair roller. If spraying, paint should be diluted with water by 10-20% as required. Two coats are recommended. Temperature at time of application and during drying should be between 10°-25°C.

Coverage: Up to 14m²/litre per coat. Coverage may vary depending upon method and rate of application and porosity of surface.

Drying times: Touch dry in 1 hour. Hard dry in 4 hours. Apply a second coat after 4 hours. Full hardness after 7 days.

Clean Up: Remove as much product as possible from application equipment before washing with water. Do not empty into drains or water courses.

Some local authorities have special facilities for the disposal of waste paint.

Limitations: Temperature at time of application and during drying should be greater than 10°C. Do not apply in direct sunlight or if rain is imminent. Not suitable for roof areas or areas where ponding water occurs, or surfaces that will be immersed in water.

Storage: Store in a dry, safe place. Do not store paint in environments where extreme temperatures may occur. Keep within 5-35°C. Do not store in direct sunlight. Whilst every effort is made to ensure the accuracy of colour, due to limitations of the print process, colour/finish shown on label is for guidance only.

*The paint film is designed to resist cracking, peeling and blistering for up to 12 years before first maintenance.

Shelf Life: 2 years (unopened) from date of manufacture. (See base of can).

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements.