

# Technical Data Sheet

Rust-Oleum Radiator Paint

---

**Rust-Oleum Radiator Paint is a stylish, tough, heat resistant finish for dated & worn radiators.**

Renovate and transform old, worn, and tired radiators with Rust-Oleum Radiator Paint. With an ultra-durable, scrubbable, smooth matt finish, it brings a new lease of life and colour to your dated and worn radiators. The paint dries in just 1 hour and can be applied directly to previously painted or primed radiators.

- **Water-based with virtually no odour.**
- **Withstands high temperatures up to 60°C.**
- **Smooth matt finish that resists scuffs & scratches.**
- **Mould & algae resistant\*.**
- **Highly concentrated.**
- **Exceptional coverage.**
- **Non-yellowing.**

**Preparation:** Ensure surface is clean, dry, and free from contamination. Bare metal surfaces should be primed with a suitable metal primer. Previously painted surfaces (*or the original factory finish*) should be abraded and degreased prior to paint application.

**Application:** Turn radiator off and allow to cool to room temperature during application and drying. Stir thoroughly before use. The product may be applied by brush or roller. If rollering, use a short to medium nap mohair roller. Two coats are recommended. Temperature at time of application and during drying should be between 10° - 25°C.

**Coverage:** Up to 14m<sup>2</sup>/l per coat.

**Drying Time:** Touch dry in 1 hour. Hard dry in 4 hours. May be over coated after 4 hours. After application of final coat allow a minimum of 4 hours before putting the radiator back into use. Run the radiator at low heat for 2 hours before gradually increasing temperature.

**Clean Up:** Remove as much product as possible from application equipment before washing with water. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste paint.

**Limitations:** Not suitable for use over chrome. Not suitable for use on towel rails. Not suitable for surfaces at temperature above 60°C.

**Shelf Life:** 2 years (unopened) from date of manufacture.  
(See base of can).

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements. A copy of the appropriate health and safety should be consulted prior to use.

*\*This product contains a biocide to protect the dry film from fungal degradation. Once dried, the paint film is classed as a treated article & contains the surface biocides 2-Octyl-2H-isothiazol-3-one 0.24% & Terbutryn 0.192% by weight. Determination of the Resistance of Surface Coatings to Mould Growth (BS3900 Part G6).*